◆□▶ ◆□▶ ◆ □▶ ◆ □▶ ● □ ● ● ●

Linux Signals and Daemons

Alessandro Barenghi

Dipartimento di Elettronica e Informazione Politecnico di Milano

barenghi - at - elet.polimi.it

May 17, 2012



By now , you should be familiar with...

- The UNIX local socket programming interface
- Locking and synchronization mechanisms
- A hint on signal handling under POSIX compliant Unices
- TCP/IP Socket programming

◆□▶ ◆□▶ ◆三▶ ◆三▶ - 三 - のへで

Lesson contents

Overview

- Asynchronous interruption mechanisms
- Signal issuing and handling
- Signal masking
- Signal safe multiplexing

Signals

Overview

- Signals are practically implemented as software triggered interrupts
- We have already seen the system utility employed to raise signals (kill)
- We will now understand how to manage signals from within a program
- We will also deal on how the delivery of signals in order to obtain interrupt free sections

Interrupts

Software what?

- Interrupts are events altering the regular execution of a program by a processor
- Can be caused by :
 - Illegal operations (e.g. divide by zero)
 - Invalid opcodes in the binary
 - Page faults
 - Software triggers (debuggers)
- The interruption of the program is instantaneous, thus process context saving issues occur

▲ロト ▲帰ト ▲ヨト ▲ヨト - ヨー の々ぐ

Interrupts

Interrupt table

- \bullet Interrupt occours \rightarrow interrupt handler is called and:
 - Immediately executed in case of hardware interrupts or...
 - Scheduled for execution immediate execution when the process resumes
- Pointer to interrupt handlers are stored in an interrupt table
- x86(_64) has 256 of them, the first one is reserved for hardware interrupts
- Linux employs the 128th to store the signal handlers for the process (int 0x80)

Interrupts

Interrupt Handling

• In order to handle an interrupt, the control unit of the CPU:

- Finds the correct interrupt vector and determines which entry has been triggered
- Checks if the interrupts handler requires a change in the privilege level
- Saves the process context (registers content and program status word)
- Loads the interrupt handler entry point and sets correctly segment selector and offsets
- The handler is finally run :)
- Interrupts can be blocked through setting a proper flag in the control unit, creating interruption safe regions

Signal Handling

- Signal handling mimicks interrupt handling :
 - Every process has an associated region of the process descriptor to track the signals sent to him
 - Upon sending a signal, the kernel updates the process descriptor of the destination process
 - The signal is received as soon as the process is selected for execution
 - Before the process is run, the kernel checks if there are any pending signal to be run
 - If the signals are not blocked, the process execution resumes from the handler instead of the previous state
 - This is repeated until all the pending signals have been dealt with

Differences

- Signal handlers are userspace code, interrupts are not
- Signal handlers may invoke system calls
- Signal handlers are not dealt with in the same instant a signal is risen
- Multiple signals of the same type may be issued before the first is dealt with
- The behaviour for multiple issues of the same signal to the same process is not defined
- Since signal handling in Linux employs the realtime signal architecture, only one signal is received

▲ロト ▲帰ト ▲ヨト ▲ヨト - ヨー の々ぐ

Signals

Signal Handling

```
The actions to be performed upon receiving a signal are specified in a signation structure :
```

```
struct sigaction {
void (*sa_handler)(int);
void (*sa_sigaction)(int, siginfo_t *,void *);
sigset_t sa_mask;
int sa_flags;
void (*sa_restorer)(void);
};
```

Signals

Signal Handling

The signal handler function void (sa_handler)(int)

- Receives as the only parameter, the number of the signal
- Does not return anything (as there is no one to return the value to)
- Can be interrupted as its running time is considered user code
- Should be kept as small as possible to minimize interruptions

Signals

Handler installation

A signal handler is installed via the sigaction primitive taking as parameters :

- The signal number signum
- A sigaction struct act containing the new handler
- A sigaction struct oldact where the old handler is saved
- The SIG_DFL macro specifies the default signal handler
- The signal handler is installed until a new one is set

Signal Masking

- It is possible to block some signals from being delivered
- A blocked signal will be delivered as soon as the block is removed^a
- The set of signal to be temporarily blocked can be specified in a sigset_t structure
- The sigemptyset function initializes an empty signal set, while the sigfillset initializes a full signal set
- The signaladdset and signaldelset respectively add and remove a signal from the set

 $^{a}\ensuremath{\mathsf{this}}$ is different from the interrupt behaviour, which, if blocked, will be ignored

Signals

Signal Masking

- Once a signal set has been built , it can be used either as a block or unblock mask
- The sigprocmask primitive adds/removes to/from the blocked signal set of the process
- The action is specified via the first parameter which can be either SIG_BLOCK, SIG_UNBLOCK or SIG_SET
- The function saves the previous signal block mask for convenience in restoring

Signals

Signal Masking

- Once a signal set has been built , it can be used either as a block or unblock mask
- The sigprocmask primitive adds/removes to/from the blocked signal set of the process
- The action is specified via the first parameter which can be either SIG_BLOCK, SIG_UNBLOCK or SIG_SET
- The function saves the previous signal block mask for convenience in restoring

Peculiarities

- Two signals cannot be blocked : KILL and STOP
- Every child inherits a copy of its parent signal mask upon the call of the fork primitive
- The signal mask is also preserved across the execve primitive
- If a signal is raised as a consequence of a hardware interrupt (e.g. SIGSEGV or SIGFPE) the kernel will take drastic actions even if the signal is masked
- It is possible to meaningfully recover from a SIGSEGV through keeping an alternate stack and restoring the correct program flow in the SIGSEGV handler

Uninterruptible multiplexing

the pselect primitive

- A critical point where signal masking may be desired is when a select function call is being run
- Masking and unmasking by hand the call via sigprocmask calls may not be as safe as desired
- To this end , the POSIX standard specifies the pselect primitive
- The primitive acts atomically as a select call encapsulated in two sigprocmask leaving the mask state in the same state it was before the call

Continuous running

Daemons

- Running a process in background is commonly called transforming it into a daemon
- A daemon is a process which runs for an undefinite amount of time (usually, until killed or the machine bursts in flames)
- By default, the daemon only communicates via logfiles as no terminal is expected to be running it
- Usually, the working directory of a daemon is the root directory (i.e. /)
- For the sake of clarity, the daemon processes have a filename ending in d (e.g. /usr/sbin/sshd)

◆□▶ ◆□▶ ◆三▶ ◆三▶ - 三 - つへで

Continuous running

the daemon primitive

- A convenient method to transform a process into a daemon is the daemon primitive
- This function accepts two integer parameters and performs the following actions :
 - Forks the running process
 - Makes the parent program call an _exit(), thus reparenting the program to init
 - If the nochdir parameter is zero, changes the working directory to /
 - If the noclose parameter is zero, closes standard input, output and error descriptors

Continuous running

Logging

- Since the daemons run in background and have no associated terminal, some way for them to communicate errors should be devised
- The most common way is to employ a log file
- In order to ease the output on the log file, usually it replaces either standard output or standard error (or both)
- This can be accomplished via the dup2 primitive
- int dup2(int oldfd, int newfd) duplicates oldfd into newfd: passing either 1 or 2 as newfd effectively replaces stdout and stderr